



Product Code: EP1/4M

EcoPro G2 1/4 Meat Counter



Features & Benefits

- High Quality 304 Stainless Steel Exterior Build Quality
- ECA Scheme Approved - as ECA products are guaranteed to be energy efficient, money can be claimed back on your investment
- Smartphone style' touch sensitive hidden until lit control pannel
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- High performance cyclopentane foam
- Airlines' ventilation system reduces compressor running time by 15%
- Take the travel out of food preparation

Shelving

| | |
|---------------------------|----------|
| 8 shelves (GN 1/1) | Standard |
| Additional S/S Trayslides | Option |
| Additional GN1/1 Shelf | Option |

Refrigeration

| | |
|-------------------------------|----------|
| R290 - Energy Efficient | Standard |
| R134a - Industry Standard | Option |
| Integral Refrigeration System | Standard |
| Less Condensing Unit | Option |
| RH Mounted Ref Unit | Option |

Specification

| | |
|-----------------------|----------|
| Meat -2/+2°C | Standard |
| Width (mm) | 2320 |
| Depth (mm) | 700 |
| Height (mm) | 865 |
| Unpacked weight (Kgs) | 162.5 |
| Packed weight (Kgs) | 191.84 |
| Gross Volume (Ltr) | 585 |
| Noise dBA @ 1m | TBC |

Base Fittings

| | |
|-------------------------------|----------|
| Remote Refrigeration System | Option |
| Castors 80mm | Standard |
| 100mm legs in lieu of castors | Option |
| Legs 150mm | Option |

Electrical & Service Data

| | |
|-------------------------|----------|
| Connect Load | 595 |
| 230/50/1 | Standard |
| Fuse Required (A) | 10 |
| Refrigerant Charge (kg) | 0.150 |

Finish

| | |
|---------------------------------|----------|
| 304 s/s ext & alu int | Standard |
| 304 s/s | Option |
| 304 S/S back for island sitting | Option |
| Worktop | Standard |

Doors

| | |
|-------|----------|
| Solid | Standard |
|-------|----------|

Product Extras

| | |
|---------------------|--------|
| Helicoil Mains Lead | Option |
| Less Worktop | Option |

Energy

| | |
|--------------------------|------|
| Global Warming Potential | 3 |
| Energy Efficiency Index | 0.00 |

Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the counter
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm



Energy



Quality



Value



Design



Hygiene



After Care

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU

Phone 08432 168800 | Email sales@foster-uk.com | Visit www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.