



The Refrigeration Experts

## Product specification



### MBCT75W: 75kg Modular Blast Chiller

17-128

Floorless modular blast chiller with 900mm door width

## Features and benefits

- 75kg chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Doors to the front and rear of the unit allow for loading and unloading from both sides
- Foster Circularair air circulation system ensures uniform chilling whilst protecting the food surface
- Robust modular construction
- Intuitive easy touch control panel – Just press and go with easy to use colour coding to indicate cycle status
- Operator-friendly fans cut-out whenever the blast chiller door is opened
- Supplied with 900mm wide door for easier loading and unloading

We use cookies to ensure you get the best experience on our website.  
[More information.](#)

Accept all

Decline all

## Technical

<b>Refrigerant</b>	R404a/449a/452a
<b>Electrical supply</b>	230/50/1
<b>Fuse rating (A)</b>	16
<b>Current (A)</b>	4.3
<b>Power (W)</b>	1080
<b>Refrigeration duty (kW)</b>	8850

## Build

<b>Finish ext/int</b>	White lam with S/S door & White foodsafe finish
<b>Section configuration</b>	Right hinge
<b>System</b>	Remote

## Dimensions

<b>Height (mm)</b>	2350
<b>Width (mm)</b>	1550
<b>Depth (mm)</b>	1330
<b>Gross volume (ltr)</b>	75
<b>Chilling capacity (kg)</b>	75
<b>Gross weight (kg)</b>	790
<b>Net weight (kg)</b>	790

## Energy

<b>Climate Class</b>	5
----------------------	---

## Options

<b>Drawer/Door material</b>	Roll through white laminate door , Roll through 304 s/s/ door
<b>Hinge</b>	Left
<b>RS485 connection for HACCP data logging</b>	Yes

## Footnotes

- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15°C e.g. Prep rooms
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral)

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | [sales@foster-gamko.com](mailto:sales@foster-gamko.com) |  
[www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.  
[More information.](#)