



The Refrigeration Experts

## Product specification



### MBCFT250: 250kg Modular Blast Chiller Freezer

17-160

Modular blast chiller/freezer with  
700mm door width complete with 25mm  
floor and integral ramp

## Features and benefits

- 250kg chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Freezing capacity from 70° to -18°C in less than 240 minutes within specifications
- Supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Foster Circular air circulation system ensures uniform chilling whilst protecting the food surface
- Robust modular construction
- Fitted with bumper bars to prevent trolley damage
- Intuitive easy touch control panel – Just press and go with easy to use colour coding to indicate cycle status
- Operator-friendly fans cut-out whenever the blast chiller door is opened

We use cookies to ensure you get the best experience on our website.  
[More information.](#)

Accept all

Decline all

## Technical

<b>Refrigerant</b>	R404a/449a/452a
<b>Electrical supply</b>	400/50/3
<b>Fuse rating (A)</b>	16
<b>Current (A)</b>	11
<b>Power (W)</b>	2550
<b>Refrigeration duty (kW)</b>	21400

## Build

<b>Finish ext/int</b>	White lam & White foodsafefinish
<b>Section configuration</b>	Right hinge
<b>System</b>	Remote

## Dimensions

<b>Height (mm)</b>	2350
<b>Width (mm)</b>	1350
<b>Depth (mm)</b>	2330
<b>Gross volume (ltr)</b>	250
<b>Chilling capacity (kg)</b>	250
<b>Freezing capacity (kg)</b>	250
<b>Gross weight (kg)</b>	790
<b>Net weight (kg)</b>	790

## Energy

<b>Climate Class</b>	5
<b>Freezing capacity (kg)</b>	250

## Options

<b>Drawer/Door material</b>	Roll through white laminate door , Roll through 304 s/s/ door
<b>Hinge</b>	Left
<b>RS485 connection for HACCP data logging</b>	Yes

## Footnotes

- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15°C e.g. Prep rooms
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral)

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | [sales@foster-gamko.com](mailto:sales@foster-gamko.com) |  
[www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.  
[More information.](#)