

Product specification



MBCFT250W: 250kg Modular Blast Chiller Freezer

17-168

Modular blast chiller/freezer with 900mm door width complete with 25mm floor and integral ramp

Features and benefits

- 250kg chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Freezing capacity from 70° to -18°C in less than 240 minutes within specifications
- Supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Doors to the front and rear of the unit allow for loading and unloading from both sides
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Robust modular construction
- Intuitive easy touch control panel Just press and go with easy to use colour coding to indicate cycle status
- Operator-friendly fans cut-out whenever the blast chiller door is

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Accept all Decline all

Technical

Refrigerant R404a/449a/452a

Electrical 400/50/3

supply

Fuse rating (A) 16

Current (A) 11

Power (W) 2550

Refrigeration 21400

duty (kW)

Build

Finish ext/int 304 S/S &

304 S/S

Section

Right hinge configuration

System

Remote

Dimensions

Height (mm) 2350

Width (mm) 1550 Depth (mm) 2330

250

790

790

Gross volume

(ltr)

Chilling 250

capacity (kg)

250 Freezing

capacity (kg)

Gross weight

(kg)

Net weight

(kg)

Energy

Climate Class

Freezing

250

5

capacity (kg)

We use cookies to ensure you get the best experience on our website. More information.

Options

Drawer/Door material Roll through white laminate door, Roll through

304 s/s/ door

Hinge Left

RS485 connection for Yes

HACCP data logging

Footnotes

- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15°C e.g. Prep rooms
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral)

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website. <u>More information.</u>