

Product specification



RBCT20/60: 60kg /20kg Roll In Blast Chiller and Freezer Cabinet

17-118

Integral roll-in blast chiller cabinet

Features and benefits

- Specific model to accept the Rational 201 trolley with a chilling capacity of 60kgs
- Chilling capacity 90°C to 3°C in less than 90 minutes within specifications. Entry temperature up to 90°C for chilling
- For ventilation and service access ensure that 400mm minimum clearance is allowed above the unit

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Accept all Decline all

Technical

Refrigerant R452a

Electrical 400/50/3

supply

Fuse rating (A) 16

Current (A) 8.2

Power (W) 5700

Refrigerant 1900

mass (g)

Build

Finish ext/int 304 S/S &

304 S/S

1

Number of

sections

Section Right hinge

configuration

System Integral

Dimensions

Height (mm) 2190

Width (mm) 980

Depth (mm) 865

Gross volume 60

(ltr)

Chilling 60

capacity (kg)

Freezing 20

capacity (kg)

Leg type Legs

Gross weight 315

(kg)

Net weight 315

(kg)

Energy

Climate Class 5

Freezing 20 capacity (kg)

GWP 2140

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Options

RS485 connection for Yes HACCP data logging

System Remote

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website. <u>More information.</u>