FOSTER
The Refrigeration Experts

Product specification



FMPRO1200NG: 613 Ltr Pro Multideck

19-144

Pro 1200mm multideck with night blind and glass end panels

Features and benefits

- Extra wide glass end panels increase display visibility
- Energy saving retracting 'soft closing mechanism' nightblind
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time
- High impact energy saving LED lighting is brighter, lasts longer and saves money in energy costs
- 2 vertical side mounted full length LED lights last on average 10 x longer than fluorescent lighting and emit a fraction of the heat output
- The Foster Pro Multideck's five display levels maximise capacity and reduce the need for frequent re-stocking
- Additional shelf depth (450mm) delivers increased volume compared to competitor cabinets
- Fully removable shelves and supports for ease of cleaning
- Supplied on roller castors as standard for ease of movement and

We use cookies to ensure you get the best experience on our website.
More information.

Accept all

Decline all

Technical

Refrigerant	R290
Temperature	Display -1/+7°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	8.5
Power (W)	1275
Refrigerant mass (g)	2x150
Thermal heat rejection (W)	1110

Build

Finish ext/int	304 S/S & 304 S/S
System	Integral

Dimensions

Height (mm)	1960
Width (mm)	1195
Depth (mm)	735
Gross volume (ltr)	613
Net volume (ltr)	446
Leg type	Roller castors
Gross weight (kg)	227
Net weight (kg)	214

Energy

Climate Class	3
Energy grade	E
EEI	61.2
AEC (kWh)	7373
GWP	3
Min - max temperature (°C)	-1/7
Energy consumption (kWh/24hr)	23.8

We use cookies to ensure you get the best experience on our website.
More information.

Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wall-sited
- Performance complies with M2 classification as prescribed in EN23953-2:2005. M2 refers to product temperatures of no greater than +7°C and no lower than -1°C when loaded in accordance with the standard and recorded under test conditions.

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com |
www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.
More information.