



The Refrigeration Experts

Product specification

FMSLIM1200NG: 466 Ltr Slim Multideck

18-153

Slimline 1200mm multideck with night blind and glass end panels

About the product

Allowing the biggest capacity from the smallest possible footprint, the **Slim Multideck** displays your products beautifully.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#).

Learn more about our [Multideck range](#)



Why choose this product

- Optimum storage and display from the smallest possible footprint
- Energy saving LED lighting is brighter, lasts longer and saves you money
- Additional shelf depth (400mm) delivers increased volume compared to competitor slimline cabinets
- Add 20mm to depth for spacer if product is to be wall-sited (required for air circulation - detachable if not wall sited)
- 1x top mounted full length LED. On average these last 10x longer than fluorescent lighting and emit a fraction of the heat output.
- Robust lockable security roller shutter with full solid end panels.
- Fully removable shelves and supports for ease of cleaning.
- Made of high quality food safe superior 'brushed' stainless steel finish for easy wipe-clean efficiency.
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time. Also our After Sales Support is there when you need us: 2 years parts and labour warranty as standard.

Specification

Technical

Temperature	Display -1/+7°C
Thermal heat rejection (W)	1275
Electrical supply	230/50/1
Current (A)	5.3
Power (W)	1275
Refrigerant mass (g)	2x150
Refrigerant	R290

Dimensions

Height (mm)	1780
Width (mm)	1195
Depth (mm)	745
Gross volume (ltr)	466
Net volume	2.29
Gross weight (kg)	207
Net weight (kg)	195

Build

Finish ext/int	304 S/S & 304 S/S
Section configuration	
System	Integral
Leg type	Roller castors

Energy

Climate Class	3
Energy grade	F
EEI	78.9
AEC (kWh)	8249
GWP	3
Min - max temperature (°C)	-1/7
Energy consumption (kWh/24hr)	23.8

Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wall-sited
- Delivery to dealer premises/direct to site on route days free of charge. Delivery and installation to ground floor site as priced - see UK price list for conditions
- Performance complies with M2 classification as prescribed in EN23953-2:2005. M2 refers to product temperatures of no greater than +7°C and no lower than -1°C when loaded in accordance with the standard and recorded under test conditions.

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.