



The Refrigeration Experts

Product specification



FFC2/1: 48 Ltr Counter Vari Temp Drawer

35-208

Variable temperature one drawer reduced width counter with splashback

About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#)

Learn more about our [FlexDrawer Counters](#)

Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate - change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works in hot kitchens, operating in ambient temperatures up to ISO Climate Class 5

Specification

| Technical | | Dimensions | |
|-----------------------------------|-------------------|---------------------------|------|
| Temperature | Freezer -18/-21°C | Height (mm) | 650 |
| Thermal heat rejection (W) | 225 | Width (mm) | 775 |
| Electrical supply | 230/50/1 | Depth (mm) | 720 |
| Current (A) | 1.35 | Gross volume (ltr) | 48 |
| Power (W) | 225 | Net volume | 48 |
| Refrigerant mass (g) | 66 | Gross weight (kg) | 88 |
| Refrigerant | R290 | Net weight (kg) | 80.5 |

| Build | | Energy | |
|------------------------------|-------------------|--------------------------------------|---------|
| Finish ext/int | 304 S/S & 304 S/S | Climate Class | 5 |
| Section configuration | | Energy grade | C |
| System | Integral | EEl | 39.27 |
| Worktop features | Splashback | AEC (kWh) | 1044.75 |
| Leg type | Braked castors | GWP | 3 |
| | | Energy consumption (kWh/24hr) | 2.86 |

Footnotes

- Adequate airflow must be kept around the counter: 50mm
- Ecodesign data relevant per compartment
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.