



The Refrigeration Experts

Product specification



EP700LL: 600 Ltr Cabinet Freezer

41-735

Dual temperature cabinet

About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#) options

Learn more about our [EcoPro G3 range](#)

Why choose this product

- This two door model offers two separate freezer storage compartments, with a dedicated refrigeration system for each
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer - all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 - the gold standard in performance stainless steel - meaning the heaviest usage touchpoints on the product are covered
- Market leading usable capacity, now supplied with 4 shelves as standard making your money go further - holds more than a conventional fridge
- Operates in ambient temperatures of up to 43°C

Specification

Technical

Temperature	Freezer -18/-21°C
Thermal heat rejection (W)	450
Electrical supply	230/50/1
Current (A)	2.6
Power (W)	450
Refrigerant mass (g)	65
Refrigerant	R290

Dimensions

Height (mm)	2080
Width (mm)	700
Depth (mm)	825
Gross volume (ltr)	270
Net volume	177.4
Gross weight (kg)	160
Net weight (kg)	150

Build

Finish ext/int	
Section configuration	
System	Integral

Energy

Climate Class	5
Energy grade	D
EEl	53.75
AEC (kWh)	1261
GWP	3
Energy consumption (kWh/24hr)	3.454

Footnotes

- Castors are not available if product is supplied less condensing unit
- 100mm clearance is required above the cabinet to allow for adequate airflow and service access
- Depth with door open is 1500mm
- This is a dual refrigeration system – data about each system can be found in the spec table above for example “Temperature” and “Temperature 2”
- Supplied without lock

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract.

Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.