



The Refrigeration Experts

Product specification



EMD1200G: 876 Ltr EcoShow Multideck

44-106

EcoShow 1200mm multideck with glass doors and end panels

About the product

With huge capacity, high impact display storage, the EcoShow Multideck is ideal for encouraging impulse purchases whilst requiring less frequent stock replenishment.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#)

Learn more about our [Multideck range](#)

Why choose this product

- EcoShow delivers an incredible 80% energy saving compared to our previous open fronted multidecks.
- Our enticing uplighting (patent pending) presents products using LED lighting with anti-glare feature to shine a light on the brands on offer.
- Fitted at no extra cost, the +stayclear condenser reduces the amount of time you need to spend maintaining your multideck and saves you money by reducing the chance of blockage and potential breakdown.
- Maximum visibility through the large glass side panels means customers no longer have to be directly in front to see your goods.
- The EcoShow range can store between 306 and 884 cans – and that's without double stacking!
- The clean aesthetic is designed to blend in with your design, giving centre stage to the products it houses. The smooth unit cover has been designed to remove the air efficiently whilst avoiding unsightly punched hole patterns.
- Doors are lockable as standard, so you can trust that your products are safe when your shop is closed for the day.
- Swivel castors as standard for easy movement – makes cleaning in and around the multideck easier than ever!

Specification

Technical

Temperature	Display -1/+5°C
Thermal heat rejection (W)	336
Electrical supply	230/50/1
Current (A)	1.45
Power (W)	336
Refrigerant mass (g)	119
Refrigerant	R290

Dimensions

Height (mm)	1955
Width (mm)	1195
Depth (mm)	770
Gross volume (ltr)	876
Net volume	2.29
Gross weight (kg)	277
Net weight (kg)	260

Build

Door material	Glass
Finish ext/int	304 S/S & 304 S/S
Section configuration	
System	Integral
Leg type	Braked castors

Energy

Climate Class	3
Energy grade	B
EEI	11.78
AEC (kWh)	1628
GWP	3
Min - max temperature (°C)	-1/5
Energy consumption (kWh/24hr)	4.46

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.