



The Refrigeration Experts

Product specification



HR200G: 200 Ltr Undercounter Cabinet Refrigerator

13-114

Glass door undercounter refrigerator cabinet (no light)

About the product

Convenient, practical and tough Undercounter Cabinets offer compact, on-the-spot storage.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#).

Learn more about our [Undercounter Cabinets](#)

Why choose this product

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- High quality magnetic door gasket
- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Supplied with glass door for optimum visibility of stored product
- Supplied on roller castors as standard for ease of movement and positioning
- Operates in ambient temperatures of up to 25°C (ISO Climate Class 3)

Specification

Technical

Dimensions

Refrigerant	R290	Height (mm)	824
Temperature	Refrigerator +3/+5°C	Width (mm)	684
Electrical supply	230/50/1	Depth (mm)	755
Fuse rating (A)	10	Gross volume (ltr)	200
Current (A)	1.2	Net volume (ltr)	98
Power (W)	225	Leg type	Roller castors rear, levelling bolts front
Refrigerant mass (g)	116	Gross weight (kg)	71
Thermal heat rejection (W)	250	Net weight (kg)	64

Build

Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Right hinge
System	Integral

Energy

Climate Class	3
Energy grade	A
EEl	9
AEC (kWh)	390
GWP	3
Min - max temperature (°C)	-1/5
Energy consumption (kWh/24hr)	1.07

Footnotes

- External cabinet depth excludes 25mm door handle
- For ventilation, ensure that 50mm clearance is allowed above and around the cabinet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.