



The Refrigeration Experts

Product specification



FPS1/3HR/101: 440 Ltr Prep Station Refrigerator

15-113

Three door gastronorm storage refrigerator prep station

About the product

Ergonomically designed and tough enough to withstand years of heavy use, Foster **Prep Stations** improve operator efficiency and increase speed of service.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#)

Learn more about our [Prep range](#)

Why choose this product

- The fan assisted, forced air system delivers even temperature holding to both the counter base and top pan storage section
- The clever inner catch tray stops food from falling into the main storage area, quickening clean down times
- Roller blind helps to maintain storage temperature in topping well
- This Prep Station has been designed with the operator in mind, with all pans and work bench height within comfortable reach
- Includes 6 x GN 1/1 shelves, along with capacity for 7 x GN 1/3 pans (or equivalent)
- Rear mounted refrigeration system maximises storage space and is easily accessible for servicing

Specification

Technical

Refrigerant

R290

Dimensions

Height (mm)

1060

| | | | |
|-----------------------------------|----------------------|---------------------------|----------------|
| Temperature | Refrigerator +1/+4°C | Width (mm) | 1440 |
| Electrical supply | 230/50/1 | Depth (mm) | 850 |
| Fuse rating (A) | 10 | Gross volume (ltr) | 440 |
| Current (A) | 5.8 | Leg type | Braked castors |
| Power (W) | 870 | GN size | 1/1 |
| Refrigerant mass (g) | 150 | Gross weight (kg) | 190 |
| Thermal heat rejection (W) | 670 | Net weight (kg) | 175 |

Build

| | |
|------------------------------|---------------------------------------|
| Finish ext/int | 304 S/S & Alu |
| Number of sections | 3 |
| Section configuration | Left hinge–Left hinge– Right hinge |
| System | Integral |
| Worktop features | Roller blind |

Energy

| | |
|----------------------|---|
| Climate Class | 4 |
| GWP | 3 |

Footnotes

- Raised pan storage area accepts pans with a maximum depth of 150mmm
- Gastronorm pans are not supplied as standard with Prep Station – please order separately
- Pan Storage Temperature +3/+5°C

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.