



The Refrigeration Experts

Product specification



MBCFT150W: 150kg Modular Blast Chiller Freezer

17-154

Modular blast chiller/freezer with 900mm door width complete with 25mm floor and integral ramp

About the product

High capacity **Modular Blast Chillers** from the Refrigeration Experts allow bulk rapid chilling without compromising food safety or quality.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#).

Learn more about our [Blast Chiller range](#)

Why choose this product

- 150kg chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Freezing capacity from 70° to -18°C in less than 240 minutes within specifications
- Supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Doors to the front and rear of the unit allow for loading and unloading from both sides
- Foster Circularair air circulation system ensures uniform chilling whilst protecting the food surface
- Robust modular construction
- Intuitive easy touch control panel – Just press and go with easy to use colour coding to indicate cycle status
- Operator-friendly fans cut-out whenever the blast chiller door is opened
- Supplied with 900mm wide door for easier loading and unloading

Specification

Technical

Refrigerant	R404a/449a/452a
Electrical supply	230/50/1
Fuse rating (A)	20
Current (A)	17.5
Power (W)	4025
Refrigeration duty (kW)	10700

Dimensions

Height (mm)	2350
Width (mm)	1550
Depth (mm)	1330
Gross volume (ltr)	150
Chilling capacity (kg)	150
Freezing capacity (kg)	150
Gross weight (kg)	790
Net weight (kg)	790

Build

Finish ext/int	White lam & White foodsafefinish
Section configuration	Right hinge
System	Remote

Energy

Climate Class	5
Freezing capacity (kg)	150

Footnotes

- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15°C e.g. Prep rooms
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral)

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.