

#### **Product specification**



# BCT15/7: 15kg/7kg Blast Chiller and Freezer

17-273

15kg Blast chiller/freezer cabinet

#### **About the product**

Foster Blast Chillers and Freezers safely control the temperature of produce to ensure that food retains its quality, taste and texture.

Available to finance with our award-winning <u>interest-free</u> <u>credit</u> and <u>leasing</u>

Learn more about our Blast Chiller range

### Why choose this product

- Chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature up to 90°C for chilling
- Freezing capacity from +70°C to -18°C in less than 240 minutes within specifications
- Dedicated 15Kg blast chiller with occasional 7Kg freeze capacity
- Exceeding UK and European food safety requirements
- High grade 304 exterior and interior the 'gold standard' in performance finishes
- Intuitive touch control panel just press and go!
- 5 Shelf Positions for GN 1/1 Pans

## Specification

Technical Dimensions

Refrigerant R290 Height (mm) 875

Electrical supply	230/50/1	Width (mm)	805
Fuse rating (A)	13	Depth (mm)	755
Current (A)	1.7	Gross volume (ltr)	106
Power (W)	400	Net volume (ltr)	105
Refrigerant mass (g)	110	Chilling capacity (kg)	15
Thermal heat rejection (W)	400	Freezing capacity (kg)	7
		Leg type	Braked castors
		GN size	1/1
		Gross weight (kg)	95
		Net weight (kg)	65

Build		Energy	
Finish ext/int	304 S/S & 304 S/S	Climate Class	5
Number of sections	1	Freezing capacity (kg)	7
Section configuration	Right hinge	GWP	3

**System** Integral

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.