

Product specification



GRL1H: 1205 Ltr Gastronorm Roll In Refrigerator

24-123

Single glass door gastronorm roll in refrigerator with floor, ramp and light

About the product

Trolley loading, high capacity **Gastronorm Roll Ins** from the Refrigeration Experts.

Available to finance with our award-winning <u>interest-free</u> <u>credit</u> and <u>leasing</u>

Learn more about our <u>Gastronorm Roll Ins</u>

Why choose this product

- Easy to clean the storage compartment has smooth surfaces and coved corners with separate fan housings
- Minimising handling of food increases the level of hygiene and food safety

- Efficient and accurate microprocessor control of storage temperature and defrost system
- Supplied with glass door for optimum visibilty of stored product
- A number of different trolley sizes can be accommodated to offer a greater choice of storage
- GN 1/1 Trolleys available with either 325mm or 530mm width tray loading. Please specify at time of order

Dimensions

Specification

Technical

Refrigerant	R290	Height (mm)	2240
Temperature	Refrigerator +1/+4°C	Width (mm)	865
Electrical supply	230/50/1	Depth (mm)	940
Fuse rating (A)	13	Gross volume (Itr)	1205
Current (A)	4.5	Leg type	Feet
Power (W)	810	GN size	2/1
Refrigerant mass (g)	135	Gross weight (kg)	183
Thermal heat rejection (W)	540	Net weight (kg)	171
Build		Energy	
Finish ext/int	304 S/S & 304 S/S	Climate Class	3
Number of sections	1	GWP	3
Section configuration	Right hinge		
System	Integral		

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.