

## **Product specification**



## FMIF120: 110kg Integral Ice Flaker

29-116

Air cooled ice flaker

## About the product

Foster Ice Flakers produce high quality flaked ice

Available to finance with our award-winning  $\underline{interest-free}$   $\underline{credit}$  and  $\underline{leasing}$ 

Learn more about our Drinks Service range

## Why choose this product

- · Innovatively designed with new user-friendly electro-mechanical controls to ensure reliability
- The models also incorporate a condenser thermostat, which ensures a full harvest of cubes
- · High output and storage capacity with dedicated storage bins
- The new flush system ensures clear ice free from impurities and eliminates the risk of lime-scale
- Output figures quoted are based on 10°C water input and ambient air temp of 21°C
- Legs provided as standard to increase height for drainage where required 70mm maximum height increase
- 110kg output per 24 hours

Specification

Technical

Dimensions

Refrigerant	R134a	Height (mm)	694
Electrical supply	220-240/50/1	Width (mm)	500
Fuse rating (A)	10	Depth (mm)	597
Current (A)	3.2	Net volume (Itr)	18
Power (W)	490	Bin Capacity (kg)	27
Refrigerant mass (g)	270	Leg type	Feet
		Gross weight (kg)	57
		Net weight (kg)	50

Build		Energy	
Finish ext/int	S/S & S/S	Bin Capacity (kg)	27
Section configuration		Climate Class	5
System	Integral	AEC (kWh)	3942
		GWP	1430
		Energy consumption (kWh/24hr)	10.8

Footnotes

• A distance of at least 20cm must be allowed between the sides, back and the walls of the machine

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.