

Product specification



XR1300L: 1300L Cabinet Freezer

33-211

Double door freezer cabinet

About the product

Affordable. Reliable. Available. XTRA by Foster.

Available to finance with our award-winning <u>interest-free</u> <u>credit</u> and <u>leasing</u>

Learn more about our XTRA Cabinets

Why choose this product

- Supplied with side integrated door handles in lieu of recessed black plastic handles.
- Robust refrigeration at an affordable price
- Microprocessor controller provides simple and accurate temperature control to ensure your food retains its quality and texture
- Hard wearing stainless steel finish to the interior and exterior is stylish and practical
- In stock and available now for immediate shipping
- Full Foster warranty included

Technical		Dimensions	
Refrigerant	R290	Height (mm)	1985
Temperature	Freezer -18/-21°C	Width (mm)	1390
Electrical supply	230/50/1	Depth (mm)	850
Fuse rating (A)	10	Gross volume (ltr)	1300
Current (A)	4	Net volume (Itr)	880.54
Power (W)	660	Leg type	Braked castors
Refrigerant mass (g)	150	GN size	2/1
Thermal heat rejection (W)	580	Gross weight (kg)	166
		Net weight (kg)	152

Build		Energy	
Cabinet type	Standard	Climate Class	5
Finish ext/int	304 S/S & 304 S/S	Energy grade	E
Number of sections	2	EEI	76.62
Section configuration	Left hinge-Right hinge	AEC (kWh)	4453
System	Integral	GWP	3
		Energy consumption (kWh/24hr)	12.199

Footnotes

Product specification available in export territories only. Please contact sales@foster-gamko.com for more information.

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.