



Product Code: BCT22-12 17-275

22Kg Blast Chiller/Freezer Cabinet



Features & Benefits

- Chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature up to 90°C for chilling
- Freezing capacity from +70°C to -18°C in less than 240 minutes within specifications
- Dedicated 22Kg blast chiller with occasional 12Kg freeze capacity
- Exceeding UK and European food safety requirements
- High grade 304 exterior and interior the 'gold standard' in performance finishes
- Intuitive touch control panel – just press and go!
- 6 Shelf Positions for GN 1/1 Pans

Base Fittings

| | |
|--------------------------|----------|
| Castors 80mm | Standard |
| Legs 100mm | Option |
| Marine Spec Legs - 150mm | Option |

Electrical & Service Data

| | |
|---|----------|
| 230/50/1 | Standard |
| 220/60/1 Electrical Supply | Option |
| RS485 connection for HACCP data logging | Option |

Doors

| | |
|-----------------------|----------|
| Solid | Standard |
| Left Hand Hinged Door | Option |

Specification

| | |
|-------------------------|----------|
| Blast Chiller/Freezer | Standard |
| Width (mm) | 755 |
| Depth (mm) | 690 |
| Height (mm) | 1530 |
| Packed weight (Kgs) | 120 |
| Chilling Capacity (Kgs) | 22 kg |
| Freezing Capacity (Kgs) | 12 kg |
| Gross Volume (Ltr) | 22 kg |

Refrigeration

| | |
|-------------------------------|----------|
| R290 - Energy Efficient | Standard |
| Integral Refrigeration System | Standard |
| Less Condensing Unit | Option |

Finish

| | |
|---------|----------|
| 304 s/s | Standard |
|---------|----------|

Footnotes

- Chilling Capacity: 22KG. Freezing capacity: 12KG 70°C to 3°C in less than 90 minutes within specifications, entry temperature up to 90°C for chilling
- Please add 55mm to depth for spacer



Energy



Quality



Value



Design



Hygiene



After Care

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU

Phone 08432 168800 | Email sales@foster-uk.com | Visit www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.