



The Refrigeration Experts

## Product specification



### EP700L: 600 Ltr Cabinet Freezer

41-723

Single door freezer marine cabinet

We use cookies to ensure you get the best experience on our website.  
[More information.](#)

Accept all

Decline all

## Features and benefits

- Suitable for marine and offshore applications, this model incorporates marine legs, bulkhead brackets, positive latch handle and marine shelves
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Market leading usable capacity, now supplied with 8 shelves as standard making your money go further – holds more than a conventional fridge
- Operates efficiently in ambient temperatures of up to 43°C

### Technical

<b>Refrigerant</b>	R290
<b>Temperature</b>	Freezer -18/-21°C
<b>Electrical supply</b>	220- 240/60/1
<b>Fuse rating (A)</b>	10
<b>Current (A)</b>	1.2
<b>Power (W)</b>	270
<b>Refrigerant</b>	80

### Build

<b>Cabinet type</b>	Marine
<b>Finish ext/int</b>	304 S/S & 304 S/S
<b>Number of sections</b>	1
<b>Section configuration</b>	Right hinge
<b>System</b>	Integral

We use cookies to ensure you get the best experience on our website.  
[More information.](#)

## Dimensions

<b>Height (mm)</b>	2080
<b>Width (mm)</b>	700
<b>Depth (mm)</b>	855
<b>Gross volume (ltr)</b>	600
<b>Net volume (ltr)</b>	479.9
<b>Leg type</b>	Marine legs
<b>GN size</b>	2/1
<b>Gross weight (kg)</b>	130.5
<b>Net weight (kg)</b>	121.5

## Energy

<b>Climate Class</b>	5
<b>Energy grade</b>	B
<b>EEI</b>	30.25
<b>AEC (kWh)</b>	1161
<b>GWP</b>	3
<b>Energy consumption (kWh/24hr)</b>	3.18

## Options

<b>Hinge</b>	Right
<b>System</b>	Remote

## Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 100mm
- Depth with door open is 1500mm

We use cookies to ensure you get the best experience on our website.  
[More information.](#)

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | [sales@foster-gamko.com](mailto:sales@foster-gamko.com) |  
[www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.  
[More information.](#)