FOSTER

The Refrigeration Experts

Product specification



XR1300H: 1300L Cabinet Refrigerator

33-210

Double door refrigerated cabinet

Features and benefits

- Supplied with side integrated door handles in lieu of recessed black plastic handles.
- Robust refrigeration at an affordable price
- Microprocessor controller provides simple and accurate temperature control to ensure your food retains its quality and texture
- Hard wearing stainless steel finish to the interior and exterior is stylish and practical
- In stock and available now for immediate shipping
- Full Foster warranty included

We use cookies to ensure you get the best experience on our website.
More information.

Accept all

Decline all

Technical

Refrigerant	R290
Temperature	Refrigerator +2/+8°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	3.6
Power (W)	510
Refrigerant mass (g)	150
Thermal heat rejection (W)	510

Build

Cabinet type	Standard
Finish ext/int	304 S/S & 304 S/S
Number of sections	2
Section configuration	Left hinge-Right hinge
System	Integral

Dimensions

Height (mm)	1985
Width (mm)	1390
Depth (mm)	850
Gross volume (ltr)	1300
Net volume (ltr)	880.54
Leg type	Braked castors
GN size	2/1
Gross weight (kg)	155
Net weight	140.5

Energy

Climate Class	5
Energy grade	E
EEI	79.13
AEC (kWh)	1627
GWP	3
Energy consumption (kWh/24hr)	4.457

We use cookies to ensure you get the best experience on our website.
More information.

Options

Footnotes

Product specification available in export territories only. Please contact sales@foster-gamko.com for more information.

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com |
www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.
More information.