

Product specification



EP2/2H: 495 Ltr Counter Refrigerator

43-348

Two door refrigerator counter

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Accept all

Decline all

Features and benefits

Technical

- A reduced footprint the more compact design of G3 counters allow them to fit in the tightest of kitchen spaces without losing capacity
- Taking the travel out of food preparation and customised to your needs, G3 counters offer unrivalled flexibility and quality.
- High performance cyclopentane foam maintains thermal efficiency for longer
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- New and improved 'Airlines' ventilation system cools the compressor which reduces running time, saving you energy
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 the gold standard in performance stainless steel meaning the heaviest usage touchpoints on the product are covered
- Racking suitable to accommodate standard bakery trays (not supplied)

Build

• Operates efficiently in ambient temperatures of up to 43°C

Refrigerant	R290	Finish ext/int	304 S/S &
Temperature	Refrigerator		Alu
	+1/+4°C	Number of	2
Electrical	230/50/1	sections	
supply		Section	Left hinge
Fuse rating (A)	10	configuration	
Current (A)	0.2	System	Integral
Power (W)	260	Worktop features	Standard
Refrigerant mass (g)	92	16414163	
Thermal heat	190		

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Dimensions

Height (mm)	865
Width (mm)	1775
Depth (mm)	800
Gross volume (ltr)	495
Net volume (ltr)	334.2
Leg type	Braked castors
Leg type GN size	
	castors
GN size Gross weight	castors 2/1

Energy

Climate Class	5
Energy grade	В
EEI	26.09
AEC (kWh)	689.85
GWP	3
Energy consumption (kWh/24hr)	1.89

Options

Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Adequate airflow must be kept around the counter: 150mm
- Depth with door open is 1113mm

We use cookies to ensure you get the best experience on our website. <u>More information.</u>

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website. <u>More information.</u>