




The Refrigeration Experts

Product specification



HR120: 120 Ltr Undercounter Cabinet Refrigerator

13-246

Reduced width undercounter refrigerator cabinet

About the product

Convenient, practical and tough Undercounter Cabinets offer compact, on-the-spot storage.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#).

Learn more about our [Undercounter Cabinets](#)

Why choose this product

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- Integrated door lock for added security
- High quality magnetic door gasket
- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- GN1/1 undercounter storage on a small footprint
- Supplied on roller castors as standard for ease of movement and positioning

Specification

Technical

Temperature	Refrigerator +1/+4°C
Thermal heat rejection (W)	160
Electrical supply	230/50/1
Current (A)	0.8
Power (W)	160
Refrigerant mass (g)	83
Refrigerant	R290

Dimensions

Height (mm)	895
Width (mm)	440
Depth (mm)	745
Gross volume (ltr)	120
Net volume	68.9
GN size	1/1
Gross weight (kg)	64
Net weight (kg)	57

Build

Finish ext/int	304 S/S & Alu
Section configuration	Right hinge
System	Integral
Leg type	Roller castors rear, levelling bolts front

Energy

Climate Class	5
Energy grade	A
EEI	14.9
AEC (kWh)	293.3
GWP	3
Energy consumption (kWh/24hr)	0.8

Footnotes

- For ventilation, ensure that 50mm clearance is allowed above and around the cabinet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.